

# SAE 20W50 API SL



## Technical Data Sheet

### PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

### DESCRIPTION:

Siddrol SAE 20W50 API SL is a fuel economy and better cold starting. Excellent engine protection in severe weather conditions. Thermal stable. Anti wear, anti oxidant and long drain interval. Low oil consumption and turbo proven stability. Oxidation resistant, good high temperature stability. Longer drain interval. Low oil consumption.

### BENEFITS:

- Excellent engine protection. Helps fuel efficiency.
- Suitable for extended drain intervals.
- Reduces chlorine content to meet the environmental requirements.
- Better cold starting.
- Reduced engine maintenance costs.

### SPECIFICATIONS:

Meets and exceeds: API SL / CF; ACEA A3/B4

### APPLICATION:

It can be used under the most difficult operating conditions (highways, congested city traffic, etc.) for every season. Recommended for all petrol engines (multi-valve and turbo types) and all diesel engines, turbo- charged or naturally aspirated in cars and light vans.

### TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	18 Cst
Kin. Viscosity @40°C	ASTM D 445	147.1
Viscosity Index	ASTM D 2270	136
Density @ 60/60F	ASTM D 1298	0.885
Pour Point	ASTM D 97	≤ -33°C
TBN	ASTM D 92	≥220°C
Antifoam	ASTM D 6034	7.28
	ASTM D 892	Pass