

SAE 5W30 API SN



Technical Data Sheet

PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Siddrol 5W-30 is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

BENEFITS:

- Its special and exclusive formula helps your vehicle maintain maximum horsepower by reducing sludge formation.
- Excellent performance for the higher power and speeds in modern engines.
- Enhances life of crankcase
- The outstanding thermal stability and resistance to oxidation of this oil prevent any degradation, even in extreme usage conditions which helps to extend engine life.
- Custom designed which helps to meet manufacturer's requirement to extend interval between oil changes.

SPECIFICATIONS:

Siddrol 5W30 SN full synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M;

Ford WSS M2C946-A, M2C929-A; Honda HTO-06, BMW: long life listing, Mercedes Benz – sheet 229.10.

APPLICATION:

SN motor oil can be used in all naturally aspirated, fuel injected, turbocharged and multivalve passenger car engines.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	11.5
Kin. Viscosity @40°C	ASTM D 445	71.7
Viscosity Index	ASTM D 2270	155
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -36°C
Flash Point	ASTM D 92	≥ 220°C
TBN	ASTM D 6034	7.25
Antifoam	ASTM D 892	Pass