

SAE 5W40 API SN



Technical Data Sheet

PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Siddrol 5W-40 SN is a premium, fully synthetic engine oil designed for modern gasoline engines, offering excellent fuel efficiency and engine protection. It is a high reach quality lubricant, completely manufactured, uniquely figured out to meet the most recent execution prerequisites of present day motors.

BENEFITS:

- Ability to lessen the effects of friction and control wear.
- Resist the accumulation of sludge, maintaining viscosity and ability to flow also preventing deposits from forming.
- Enhanced cold start-up performance.
- Custom designed which helps to meet manufacturer's requirement to extend interval between oil changes.

SPECIFICATIONS:

Siddrol 5W40 SN full synthetic motor oil meets and exceeds the requirements of all major car manufacturers and the following standards:

ILSAC GF-5; ACEA A5/B5; Chrysler 6395; GM 6094M, 4718M;

Ford WSS M2C946-A, M2C929-A; Honda HTO-06, BMW: long life listing, Mercedes Benz – sheet 229.10.

APPLICATION:

This product meets or exceeds the requirements of the latest API and ILSAC industry specifications for petrol and hybrid engine oils, as well as the requirements of many major American engine manufacturers. Suitable for use in passenger cars.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Neutral
Kin. Viscosity @100°C	ASTM D 445	14 Cst
Kin. Viscosity @40°C	ASTM D 445	92.85 Cst
Viscosity Index	ASTM D 2270	155
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -39°C
Flash Point	ASTM D 92	≥ 220°C
TBN	ASTM D 6034	7.6
Antifoam	ASTM D 892	Pass