

SAE 85W140 API GL-5



Technical Data Sheet

PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Siddrol SAE 85W140 is a high-performance multigrade, high-pressure gear oil manufactured from high quality mineral base oils and multi-functional extreme pressure additives. It provides excellent low temperature fluidity for safe lubrication during very low temperature transmission and trans axle startup, and also maintains a thick protective oil film during extremely hot operating conditions.

BENEFITS:

- Excellent wet gear performance, shifting and anti-shudder durability.
- Excellent steel-on-steel frictional engagement with good torque transfer capability.
- Maximum equipment life that protects against wear, corrosion, and the formation of harmful deposits.
- Extended drain intervals due to improved oxidation resistance.
- Resistance to oxidation and oil thickening and are compatible to oil seals.

SPECIFICATIONS:

Siddrol Gear Oil 85W140 API GL-5 meets or exceeds following International and Builder specifications

Gear lubes meets the performance requirement of API service GL-5 and U.S Military specification MIL-L-2105C.

APPLICATION:

For use in applications requiring API GL-5 performance such as heavy-duty differentials, axles, and final drives where extreme pressures and shock loading are expected.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Kin. Viscosity @100°C	ASTM D 445	25.75 - 31.5 Cst
Viscosity Index	ASTM D 2270	100
Density @ 60/60F	ASTM D 1298	0.890
Pour Point	ASTM D 97	≤ -21°C
Flash Point	ASTM D 92	≥ 270°C
Antifoam	ASTM D 892	Pass