

ATF DEXRON IV



Technical Data Sheet

PACKAGING:

1L, 4L, 5L, 7L, 20L, 25L, 60L, 208L

DESCRIPTION:

Siddrol Dexron III ATF is approved for use in all General Motors automatic transmissions. It is licensed against Dexron® VI which supersedes all previous Dexron® specifications for General Motors Holden applications.

BENEFITS:

- Low viscosity formulation provides fuel economy benefits compared with fluids formulated to meet Dexron® IIIH or earlier specifications.
- Premium synthetic formulation gives Outstanding oxidative resistance extending transmission life.
- Enhanced friction durability improves shifting performance.

SPECIFICATIONS:

Dexron III meets or exceeds following International and Builder specifications Allison C-4 Fluids, Allison TES, 389, Caterpillar TO-2 Fluids Chrysler transmissions prior to Chrysler MS-9602 or MS-7176, Ford MERCON®, Ford M2C138-CJ, M2C 166-H Fluids, GM DEXRON® III-H, III-G, III-F, III-E, III-D MAN 339 Z1 and V1, Z2 and V2, MB 236.1, 236.5, 236.6, 236.7, 236.9, Voith 55,6335 and 55, 6336, Volvo 97340, 97341, ZF TE-ML 02F, 03D, 04D, 09, 11A/B,14A/B, 16L, 17C

APPLICATION:

ATF is particularly suitable for use in automatic transmissions of car & light trucks and On-highway & Off-highway heavy-duty automatic transmissions. It is also recommended for power steering, torque converters and hydraulic systems, where such types of fluids are specified.

TYPICAL PROPERTIES:

TEST	FREQUENCY	RESULT
Appearance	VISUAL	Bright & Clear
Color	ASTM D 1500	Red
Kin. Viscosity @100°C	ASTM D 445	7-9
Kin. Viscosity @40°C	ASTM D 445	30.2
Viscosity Index	ASTM D 2270	185
Density @ 60/60F	ASTM D 1298	0.850
Pour Point	ASTM D 97	≤ -49°C
Flash Point	ASTM D 92	≥ 220
Water Content	ASTM D 6034	-ve
Antifoam	ASTM D 892	Pass